

Safety Data Sheet according to Regulation (EC) No. 453/2010

according to Regulation (EC) No. 453/2010 0.9% vol Iso-Butane/ Air Date of issue: 24/02/2015 Revision date:



:

Danger

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	 Industrial and professional. Perform risk assessment prior to use. Test gas/Calibration gas. Laboratory use. Contact supplier for more information on uses.
Uses advised against	: Consumer use.
1.3. Details of the supplier of the safety d	lata sheet
Company identification	: SEMA Gases
	Driemanssteeweg 190
	3084 CB Rotterdam
1.4. Emergency telephone number	
Emergency telephone number	: 0031 (0)10 293 88 88 Emergency telephone number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Physical hazards

Gases under pressure : Compressed gas

H280

Not classified as dangerous substance / mixture.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms (CLP) :



Signal word (CLP) Hazard statements (CLP)

. H280 - Contains gas under pressure; may explode if heated.

Precautionary statements (CLP)

: Danger



- Storage : P403 - Store in a well-ventilated place.

2.3. Other hazards

: None.

SECTION 3: Composition/information on ingredients

3.1. Substance : Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Nitrogen	(CAS No) 7727-37-9 (EC no) 231-783-9 (EC index no) (REACH-no) *1	78.28 9	Not classified	Press. Gas Comp., H280
Oxygen	(CAS No) 7782-44-7 (EC no) 231-956-9 (EC index no) 008-001-00-8 (REACH-no) *1	20.81 1	O; R8	Ox. Gas 1, H270 Press. Gas Comp., H280
Isobutane	(CAS No) 75-28-5 (EC no) 200-857-2 (EC index no) 601-004-00-0 (REACH-no) 01-2119485395-27	0.9	F+; R12	Flam. Gas 1, H220 Press. Gas Liq., H280

Full text of R- and H-phrases: see section 16

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*2: Registration deadline not expired.

*3: Registration not required: Substance manufactured or imported < 1t/y.

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation	: Adverse effects not expected from this product.
- Skin contact	: Adverse effects not expected from this product.
- Eye contact	: Adverse effects not expected from this product.
- Ingestion	: Ingestion is not considered a potential route of exposure.
4.2. Most important syn	nptoms and effects, both acute and delayed
	: Refer to section 11.

4.3. Indication of any immediate medical attention and special treatment needed

: None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

 Suitable extinguishing media Unsuitable extinguishing media 	: Water spray or fog. : Do not use water jet to extinguish.
5.2. Special hazards arising from the	substance or mixture
Specific hazards	: Exposure to fire may cause containers to rupture/explode.
Hazardous combustion products	: None.
FO Advise for first first term	

5.3. Advice for fire-fighters



0.9% vol Iso-Butane/ Air

Specific methods

Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
 If possible, stop flow of product.
 Use water spray or fog to knock down fire fumes if possible.
 Move containers away from the fire area if this can be done without risk.

SECTION 6: Accidental release measures

<u>6.1.</u>	Personal precautions, protective equipment and emergency procedures
	: Try to stop release. Act in accordance with local emergency plan. Stay upwind.

6.2. Environmental precautions

: Try to stop release.

6.3. Methods and material for containment and cleaning up

: None.

6.4. Reference to other sections

: See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product	 The substance must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularily) checked for leaks before use. Do not smoke while handling product. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not breathe gas. Avoid release of product into atmosphere.
Safe handling of the gas receptacle	 Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. Containers should be stored in the vertical position and properly secured to prevent them from falling over.
7.2 Conditions for safe storage i	ncluding any incompatibilities

7.2. Conditions for safe storage, including any incompatibilities



Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over.
Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place.
Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.

7.3. Specific end use(s)

: None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

0.9% vol Iso-Butane/ Air			
OEL : Occupational Exposure	Limits		
EU	TWA IOELV (EU) 8 h [mg/m ³]	<	

DNEL (Derived-No Effect Level) : No data available.

PNEC (Predicted No-Effect Concentration) : No data available.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

	 Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Consider work permit system e.g. for maintenance activities.
8.2.2. Individual protection	n measures, e.g. personal protective equipment
	: A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.
Eye/face protection	: Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection.
Skin protection	
- Hand protection	: Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk.
- Other	: Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
 Respiratory protection 	 Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Thermal hazards	: None necessary.
8.2.3. Environmental expo	sure controls
~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	<ul> <li>Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.</li> </ul>

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties



# 0.9% vol Iso-Butane/ Air

#### Appearance

- Physical state at 20°C / 101.3kPa ٠

: Gas.

• Colour	<ul> <li>Mixture contains one or more component(s) which have the following colour(s): Colourless.</li> </ul>
Odour	<ul> <li>Colouries.</li> <li>There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure.</li> <li>Mixture contains one or more component(s) which have the following odour(s):</li> </ul>
Odour threshold	Stenchant often added. Sweetish. Odour threshold is subjective and inadequate to warn of overexposure.
pH value	: Not applicable for gas-mixtures.
Molar mass	: Not applicable for gas-mixtures.
Melting point	: Not applicable for gas-mixtures.
Boiling point	: Not applicable for gas-mixtures.
Flash point	: Not applicable for gas-mixtures.
Evaporation rate (ether=1)	: Not applicable for gas-mixtures.
Flammability range	: Non flammable.
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Relative density, gas (air=1)	: Lighter or similar to air.
Solubility in water	: Solubility in water of component(s) of the mixture :
Partition coefficient n-octanol/water [log Kow]	Isobutane: 54 mg/l     Nitrogen: 20 mg/l     Oxygen: 39 mg/l     Not applicable for gas-mixtures.
Auto-ignition temperature	: Non flammable.
Viscosity [20°C]	: Not applicable.
Explosive Properties	: Not applicable.
Oxidising Properties	: Not applicable.
9.2. Other information	
Other data	: None.

# **SECTION 10: Stability and reactivity**

<u>10.1.</u>	Reactivity	
10.2.	Chemical stability	: No reactivity hazard other than the effects described in sub-sections below.
		: Stable under normal conditions.
<u>10.3.</u>	Possibility of hazardous reactions	
10.4		: None.
<u>10.4.</u>	Conditions to avoid	: None.
<u>10.5.</u>	Incompatible materials	
		: None.
<u>10.6.</u>	Hazardous decomposition products	
		: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity

: Classification criteria are not met.



Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

Assessment

: Classification criteria are not met.

Isobutane (75-28-5)	
EC50 48h - Daphnia magna [mg/l]	16.3 mg/l
EC50 72h - Algae [mg/l]	8.6 mg/l
LC50 96 h - fish [mg/l]	28 mg/l
12.2. Persistence and degradability	
Assessment	: No data available.
12.3. Bioaccumulative potential	
Assessment	: No data available.
12.4. Mobility in soil	
Assessment	: No data available.
12.5. Results of PBT and vPvB assess	nent
Assessment	: Not classified as PBT or vPvB.
12.6. Other adverse effects	
Effect on the ozone layer	: None.
Effect on global warming	: No known effects from this product.
Ellect on global warning	
SECTION 13: Disposal considerati	ons
13.1. Waste treatment methods	
15.1. Waste treatment methods	Operate at some live if we identicate in some install
	Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous.
	Pour plus de recommandation sur les méthodes d'élimination des gaz, se référer au code de
	bonnes pratiques de l'EIGA Doc 30 " Disposal of gases", téléchargeable sur
	http://www.eiga.org.
List of hazardous waste codes (from Commission Decision 2001/118/EC)	: 16 05 04: Gases in pressure containers (including halons) containing dangerous substances.
13.2. Additional information	
	: None.



SECTION 14: Transport information		
<u>14.1. UN number</u>		
UN-No.	: 1950	
14.2. UN proper shipping name		
Transport by road/rail (ADR/RID)	: AEROSOLS, ASPHYXIANT	
Transport by air (ICAO-TI / IATA-DGR)	: AEROSOLS, NON – FLAMMABLE	
Transport by sea (IMDG) 14.3. Transport hazard class(es)	: AEROSOLS	
Labelling		
	2.2 : Non-flammable, non-toxic gases	
Transport by road/rail (ADR/RID)		
Class	: 2	
Classification code	: 5A	
Hazard identification number Tunnel Restriction	: 20 : E - Passage forbidden through tunnels of category E	
	. L - Passage follolduen through turners of category L	
Transport by air (ICAO-TI / IATA-DGR) Class / Div. (Sub. risk(s))	: 2.2	
Transport by sea (IMDG)		
Class / Div. (Sub. risk(s))	: 2	
Emergency Schedule (EmS) - Fire	: F-D	
Emergency Schedule (EmS) - Spillage	: S-U	
14.4. Packing group		
Transport by road/rail (ADR/RID)	: Not applicable	
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable	
Transport by sea (IMDG)	: Not applicable	
14.5. Environmental hazards		
Transport by road/rail (ADR/RID)	: None.	
Transport by air (ICAO-TI / IATA-DGR)	: None.	
Transport by sea (IMDG)	: None.	
14.6. Special precautions for user		
Packing Instruction(s)	. 0007	
Transport by road/rail (ADR/RID)	: P207	
Transport by air (ICAO-TI / IATA-DGR) Passenger and Cargo Aircraft	: 203	
i assenger and Cargo Allorati	. 200	



# 0.9% vol Iso-Butane/ Air

Cargo Aircraft only	: 203
Transport by sea (IMDG)	: P207
Special transport precautions	<ul> <li>Avoid transport on vehicles where the load space is not separated from the driver's compartment.</li> <li>Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.</li> <li>Before transporting product containers: <ul> <li>Ensure there is adequate ventilation.</li> <li>Ensure that containers are firmly secured.</li> <li>Ensure cylinder valve is closed and not leaking.</li> <li>Ensure valve outlet cap nut or plug (where provided) is correctly fitted.</li> </ul> </li> </ul>

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable

SECTION 15: Regulatory information		
15.1. Safety, health and environmental r EU-Regulations	egulations/legislation specific for the substance or mixture	
Seveso directive 96/82/EC	: Not covered.	
<b>National regulations</b> National legislation Water hazard class (WGK)	: Ensure all national/local regulations are observed.	
15.2. Chemical safety assessment	: A CSA does not need to be carried out for this product.	
SECTION 16: Other information		

Indication of changes	: Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.
Training advice	: Receptacle under pressure.
Further information	<ul> <li>This Safety Data Sheet has been established in accordance with the applicable European Union legislation. Classification in accordance with calculation methods of regulation (EC) 1272/2008 CLP / (EC) 1999/45 DPD.</li> </ul>

### Full text of R-, H- and EUH-phrases

Flam. Gas 1	Flammable gases, Category 1
Ox. Gas 1	Oxidising Gases, Category 1
Press. Gas Comp.	Gases under pressure : Compressed gas
Press. Gas Liq.	Gases under pressure : Liquefied gas
H280	Contains gas under pressure; may explode if heated
R12	Extremely flammable
R8	Contact with combustible material may cause fire
F+	Extremely flammable
0	Oxidising

damage resulting from its use can be accepted.

### DISCLAIMER OF LIABILITY

ſ

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or